

Splitter Distribution Box / Optical Distribution Point Solid

08

Termination Box HTTP-X16B

Specifications

1. Accommodate PLC Splitter Module
2. Anti-UV (Ultra Violet)
3. 3 inlet ports, 16 outlet ports
4. Ability to store uncut cables
5. Economic design with plastic adaptor panel
6. Accommodate SC/APC, SC/UPC adaptor
7. It is applicable for wall-mounted, indoor or outdoor
8. Max capacity (F) : 4F

Applications

1. FTTH access network
2. Telecommunication network
3. CATV Networks
4. Data communications network
5. Local Area Networks
6. Wall-mounted, Indoor or Outdoor

Item	Dimension (mm)	Cable Port	PLC Splitter	Protection Class
HTTP-X16B	344 x 294 x 90 mm	3 cable ports (for cables with max diameter 15mm) + 16 drop cable ports	2 pcs of 1 x 8 Blade type (LGX type) Splitter	IP 55

Office Address

PT. INFOTEL MANDIRI

Jl. Kaji No. 33 H - I, Petojo Utara
Gambir - Jakarta Pusat
Telp. +62 21 631 1661
Email. info@infotel.co.id
www.infotel.co.id

Workshop Address

PT. INFOTEL MANDIRI

Jl. Cibenter 14, Cukanggalih
Curug - Kab. Tangerang

